

Cable Drum, Tubing and Container Trailers

Type BKT 10 to BKT 15



Type BKT 10-12-15



The BKT 10 - 15 Trailer is loaded by two tiltable jibs with manually operated hydraulic pump and two double acting hydraulic cylinders. Upon request, all trailers may be delivered with extendible loading jibs for picking up tube reels. Larger diameters of pipe coils than mentioned for the cable drums can be transported with that additional extensions.

The trailers of both construction series are hot-galvanised.

Type BKT 10K-12K-15K

The loading frame is tilted up with a non-recoiling, hand-operated windlass and secured with a bolt. Upon request, all trailers may be delivered with extendible loading jibs for picking up tube reels.



BKT 10K with reel RH 63

Technical Data:

-o single-straight

-o single-height-adjustable

Type	Pay load	Empty weight	Total weight	Max. drum dia.	Loading width	Chassis		Length	Width	Height	Order No.
						Type	Brake				
BKT 10	900 kg	400 kg	1300 kg	1800 mm	1400 mm	-o	overrun	3200 mm	2000 mm	1600 mm	008.020.00
BKT 12	1150 kg	450 kg	1600 kg	2000 mm	1500 mm	-o	overrun	3200 mm	2200 mm	1700 mm	008.021.00
BKT 15	1500 kg	500 kg	2000 kg	2500 mm	1600 mm	-o	overrun	3400 mm	2300 mm	1850 mm	008.022.00
BKT 12/15	1140 kg	460 kg	1600 kg	2500 mm	1580 mm	-o	overrun	3680 mm	2260 mm	1940 mm	008.740.00

BKT 10	900 kg	400 kg	1300 kg	1800 mm	1400 mm	-o	overrun	4000 mm	2000 mm	1600 mm	008.020.01
BKT 12	1150 kg	450 kg	1600 kg	2000 mm	1500 mm	-o	overrun	4050 mm	2200 mm	1700 mm	008.021.01
BKT 15	1500 kg	550 kg	2050 kg	2500 mm	1600 mm	-o	overrun	4200 mm	2300 mm	1850 mm	008.022.01

BKT 10K	950 kg	350 kg	1300 kg	1800 mm	1400 mm	-o	overrun	3200 mm	2000 mm	1600 mm	008.015.00
BKT 12K	1200 kg	400 kg	1600 kg	2000 mm	1500 mm	-o	overrun	3200 mm	2200 mm	1850 mm	008.016.00
BKT 15K	1500 kg	500 kg	2000 kg	2500 mm	1600 mm	-o	overrun	3400 mm	2300 mm	1900 mm	008.017.00

BKT 10K	950 kg	350 kg	1300 kg	1800 mm	1400 mm	-o	overrun	4000 mm	2000 mm	1600 mm	008.015.01
BKT 12K	1200 kg	400 kg	1600 kg	2000 mm	1500 mm	-o	overrun	4050 mm	2200 mm	1850 mm	008.016.01
BKT 15K	1500 kg	550 kg	2050 kg	2500 mm	1600 mm	-o	overrun	4200 mm	2300 mm	1900 mm	008.017.01

Specifications are subject without notice. Output details are depending on use conditions.



Cable drum trailer type BKT 15

The special loading platform is based on the standard container with a capacity of 1,6m³, order no. 030.101.00. The two pick-up jibs operated by a hydraulic hand pump, will swing out the platform out behind the trailer.



Cable drum trailer type BKT 10 with a hydraulic power pack (4 kW) and a single arm cable drum drive for fibre optic cables.

Further additional outfit is the steel axle with extensions for picking up drums of diameters less than 800mm.



Cable drum trailer type BKT 12/15 with extendible pick-up jibs and tube coil cage RH 160

The pick-up jibs and the cage may be adjusted to coil diameters of up to 3700mm. After the packing straps have been removed from the coil, the tube can be uncoiled out of the centre.

Capacity: tube-Ø 90-160mm, max. length: 100m



Cable drum trailer BKT 15 with container 1,6 m³

The container has a capacity of 1,6m³ and is equipped with lockable cover, order no. 030.101.50.

Specifications are subject without notice. Output details are depending on use conditions.