

Cable Drum Transport and Laying Trailer

Type BTT 5825 – BTT 7525



BTT 5825 / 7525 with optional extras

BTT 5825 / 7525

The U-shaped structure of the trailer with its open rear allows the be backing directly to the position of the cable drum. After the drum shaft has been pushed through the centre bore of the drum and engaged into the appropriate carrying pockets of the trailer, the drum is lifted hydraulically and ready for transport and unreeling. With the standard version, the drum is lifted by hydraulic hand pump via two individually controllable cylinders. Additional carrying pockets for smaller drums are delivered as standard accessories.

Optional extras:

power hydraulic system for lifting and rotating the drum



BTT 5825M / 7525M

The BTT 5825M and 7525M trailer differs from the BTT 5825/7525 type only in the method of loading. With this type the drum carriers are lifted with a hand-operated windlass, which can also be used for hauling the cable drum into the trailer, where the ground does not allow the trailer to be backed to the drum.

Optional extras:

power hydraulic system for lifting and rotating the drum

BTT 5825 M / 7525 M trailer with extras:

- power hydraulic windlass
- power hydraulic drum drive
- special finish

Max. towing speed: 25 km/h.

Trailers for higher towing speeds upon request.

Finish: Traffic red RAL 3020

Technical data:

-o single axle straight

-o single axle height adjustable

Type	Pay load	Empty weight	Total weight	Max. drum dia.	Loading width	Chassis		Length	Width	Height	Order No.
						Type	Brake				
BTT 5825	5800 kg	1150 kg	6950 kg	3200 mm	1720 mm	-o	Air-press	4000 mm	2520 mm	2300 mm	028.600.00
BTT 5825 M	5800 kg	1150 kg	6950 kg	3200 mm	1720 mm	-o	Air-press	4000 mm	2520 mm	2300 mm	028.600.50
BTT 7525	7500 kg	1150 kg	8650 kg	3200 mm	1720 mm	-o	Air-press	4000 mm	2520 mm	2300 mm	028.601.01
BTT 7525 M	7500 kg	1150 kg	8650 kg	3200 mm	1720 mm	-o	Air-press	4000 mm	2520 mm	2300 mm	028.601.51

Specifications are subject without notice. Output details are depending on use conditions.

Bagela

Cable Drum Transport and Laying Trailer Type BTT 8020E



BTT 8020 E

The model BTT 8020 E is based on the previous models. This version is reduced to the minimum of outfit to keep the price low as possible.

Optional extras:

- power pack for the hydraulic system
- cable drum drive
- lightning system
- mudguards
- additional pilot lifts



Serial outfit:

- supporting wheel
- manual hydraulic pump with 2 hydraulic cylinders which are single controlled
- steel axle diameter 76mm with two fixing clamps
- trailer will delivered in a dismantled version
- manual parking brake
(without lightning-, brake system and mudguards)



BTT 5825/7525/8020E – export version

All trailers of the BTT series are available as a collapsible version, which reduces loading space and freight charges.

Technical data:

-o single axle straight

-o single axle height adjustable

Type	Pay load	Empty weight	Total weight	Max. drum dia.	Loading width	Chassis		Length mm	Width mm	Height mm	Order No.
						Type	Brake				
BTT 8020E	8000 kg	1100 kg	9100 kg	3200 mm	1720 mm	-o	only for parking	4000	2520	2300	028.601.30

Specifications are subject without notice. Output details are depending on use conditions.